

Thank you for your interest in the 8" jointers tool review from issue 168 of WOOD® magazine.

Please note this chart is only part of the review. To download the complete 7-page review visit the WOOD Store at www.woodstore.net

THE STRAIGHT SCOOP ON EIGHT 8" JOINTERS

BRAND	MODEL	MOTOR		SWITCH		CUTTERHEAD				TABLE				FENCE		PERFORMANCE GRADES (13)			ACCESSORIES (14)		WARRANTY (YEARS)	COUNTRY OF ASSEMBLY (15)	SELLING PRICE (16)				
		VOLTAGE (1)	AMPERAGE AT 110V, 220V (2)	TYPE (3)	LOCATION (4)	KNIFE STYLE (5)	KNIFE MATERIAL (6)	MAXIMUM WIDTH OF CUT (INCHES)	SPEED (RPM) (7)	BED LENGTH (INCHES) (8)	INFEE TABLE ADJUSTMENT TYPE (9)	OUTFEED TABLE ADJUSTMENT TYPE (9)	MAXIMUM CUTTING DEPTH (INCHES) (10)	DEPTH-OF-CUT LIMITER (YES/NO)	FENCE SIZE (L X H, INCHES)	FRONT-TO-REAR ADJUSTMENT TYPE (11)	TILT ADJUSTMENT TYPE (12)	CUT QUALITY	TABLE ADJUSTMENT EASE	FENCE ADJUSTMENT EASE				BLADE CHANGING EASE	ACCESSIBILITY OF CONTROLS	STANDARD	OPTIONAL
CRAFTSMAN	21703	220	8.6	M	B	ST	S	8½	5,181	71	H	H	½	Y	40x4¾	S	M				D,K,P		8	420	1	C	\$1,150
DELTA	37-350A	110/220	16.3, 8.1	N	B	ST	S	8½	5,588	72¾	L	L	¾	N	35x5	S	M				D,P	M	6	394	2	C	\$1,100
GRIZZLY	G0593	110/220	24, 12	M	C	SI	C	8	5,782	75½	H	H	½	N	38x4	R	M				D,K,P	M	8½	418	1	C	\$995
JET	JJ-8CS	220	12	M	B	ST	S	8½	5,737	62¼	H	H	½	N	38x4	S	M				D,K,P	M	5½	398	5	T	\$1,200
POWERMATIC	PJ-882 (1610079)	220	9	M	C	ST	S	8½	7,169	83½	L	L	½	Y	38x4¾	S	H				D,K,P		5½	610	5	T	\$1,650
SHOP FOX	W1705	220	12	M	C	SI	C	8	5,692	70½	H	H	½	N	40x5	S	M				D,E,P	M	10	465	2	T	\$1,395
SUNHILL	CT-204L (w/spiral)	220	12	M	B	H	S	8½	5,672	73½	H	H	½	N	38x4	S	M				K		5½	470	1	T	\$1,000
YORKCRAFT	YC-8J	110/220	22, 11	N	C	RI	C	8	5,588	72¾	L	H	½	Y	35x5	R	M				D,E,M,P		6	500	1	C	\$1,050

Note: To view the performance ratings, you must purchase the complete review, available at www.woodstore.net

- | | | | | | |
|--|--|---|---|---|---|
| <p>1. All wired from the factory for 220 volts. All testing conducted at 220 volts.</p> <p>2. According to manufacturer's specifications.</p> <p>3. (M) Magnetic
(N) Nonmagnetic</p> | <p>4. (B) Base
(C) Column</p> <p>5. (H) Helical knives
(RI) RADIUS inserts
(SI) Square inserts
(ST) Straight knives</p> <p>6. (C) Carbide
(S) High-speed steel</p> | <p>7. Measured by phototachometer under no load.</p> <p>8. Infeed and outfeed tables are the same length on all models except Delta. The Delta infeed table makes up 43½" of its 72¾" total bed length.</p> <p>9. (H) Handwheel
(L) Lever</p> | <p>10. For rabbeting only. Manufacturers recommend removing no more than ¼" of material when face- or edge-jointing.</p> <p>11. (R) Rack-and-pinion gear
(S) Slide-in keyway</p> <p>12. (H) Handwheel control
(M) Manual tilt</p> | <p>13. A Excellent
B Good</p> <p>14. (D) 4" dust port
(E) Extra inserts
(K) Knife-setting gauge
(M) Mobile base
(P) Push blocks</p> | <p>15. (C) China
(T) Taiwan</p> <p>16. Prices current at time of article production and do not include shipping where applicable.</p> |
|--|--|---|---|---|---|